

PH30







Precision easy operation: all functions operated in one hand.

Large LCD with backlight, Multi-line display for easy reading, Auto-Power Off saves battery after 5 mins non-use.

1*1.5V AAA long battery life

Easy maintenance, simple to change battery and electrode

Floats on water, IP67 rated

Field throw measurement (Auto Lock Function)



Fun of Measuring

Comes from extensive applications: PH30 meet your water measurement needs from 1ml micro sample testing to field throw measurement, skin or paper pH testing, etc.



CLEAN PH30 pH Tester

- · Extensive applications: meet your water measurement needs from 1 ml micro sample testing to field throw measurement, skin or paper pH testing.
- User replaceable high-impedance plane electrode.

Range	-2.00 ~ +16.00 pH
Resolution	0.01 pH
Accuracy	± 0.01 pH
Temp. Range	0 - 100.0 °C / 32 - 212 °F
Temp. Resolution	0.1 °C / 1 °F
Calibration Point	Up to 3 (auto recognized)
pH Buffer Kinds	USA - pH 4.01, 7.00, 10.01
	NIST - pH 4.01, 6.86, 9.18
Electrode	CS1930 plane pH electrode
Temp. Compensation	Auto / Manual
LCD	20 * 30 mm multi-line crystal display
Protection	IP67
Auto backlight off	30 Seconds
Auto power off	5 minutes without key be pressed
Power	1*1.5V AAA battery
Dimensions	(H×W×D) 185×40×48 mm
Weight	95 g